

(19)



Canadian
Intellectual Property
Office

An Agency of
Industry Canada

Office de la Propriété
Intellectuelle
du Canada

Un organisme
d'Industrie Canada

(11) **CA 2 326 118**(13) **A1**

(40) 20.05.2001

(43) 20.05.2001

(12)

(21) **2 326 118**(51) Int. Cl. 7: **B65D 6/18**(22) **17.11.2000**(30) **09/444,148 US 20.11.1999**

(71)

**REHRIG PACIFIC COMPANY,
4010 East 26th Street, LOS ANGELES, XX (US).**

(72)

**HSU, ROGER S. (US).
KOEFLDA, GERALD R. (US).**


(74)

MACRAE & CO.

(54) **PRESENTOIR DE PROMOTION DEMONTABLE**(54) **COLLAPSIBLE MERCHANDISING CONTAINER**

(57)

A collapsible display container includes a base and a pair of opposed side walls each pivotably attached to the base. The side walls are orientable between an assembled position and a second position. At least one of the side walls includes a display member which is mounted to it. The display member is movable between an open position and a closed position. Thus, when the display member is in the open position and the at least one side wall is in the assembled position, the interior of the container is accessible through the at least one side wall.



Abstract

5 A collapsible display container includes a base and a pair of opposed side walls each pivotably attached to the base. The side walls are orientable between an assembled position and a second position. At least one of the side walls includes a display member which is mounted to it. The display member is movable between an open position and a closed position. Thus, when the display member is in the open position and the at least one side wall is in the assembled position, the interior of the container is accessible through the at least one side wall.

COLLAPSIBLE MERCHANDISING CONTAINER

TECHNICAL FIELD

This invention relates to a multi-purpose collapsible merchandising
5 container adaptable for the storage, transport, and display of produce items and other
goods.

BACKGROUND ART

Collapsible containers and crates are commonly used to transport and
store a variety of items. Such crates are typically formed of injection molded plastic
10 and are frequently adapted to receive perishable food items, such as produce. When
assembled, such containers are rectangular in shape and have a flat base surrounded
by four upstanding side panels which are joined to the flat base. When the
containers are not in use, the collapsible feature of the containers allows the
containers to be folded or otherwise reduced in size, thereby providing a desired
15 compact size when storage space is minimal.

Current collapsible containers, however, are not well suited for
displaying its contents, particularly at the point of sale. The task of investigating the
contents of a particular collapsible container is even more arduous in a situation
where the containers are stacked upon each other. Under these circumstances, the
20 containers must typically be unstacked in order to discover and access its contents.

Consequently, there is a need for an improved collapsible container
which is suitable for display purposes. The improved container should allow for
enhanced visibility of the contents of the container, as well as access to the contents
of the container. The improved container should also be capable of stacking with
25 similar containers when assembled and nested with similar containers when folded.
The container should also allow for visibility and access under conditions where the

containers are stacked. The container should also have a sturdy construction and load-bearing properties.

DISCLOSURE OF INVENTION

5 It is an object of the present invention to provide a collapsible merchandising display container which provides for access to the contents of the container, particularly when the container is in a stacked orientation with a similar container or when conventional access to the container through its upper opening is difficult or inconvenient.

10 It is another object according to the present invention to provide a collapsible display container which provides access and visibility to the contents of the container from the side, even when the side walls of the container are in an assembled and up orientation.

15 It is still another object according to the present invention to provide a collapsible display container which incorporates an access panel to the contents of the container which is movable between an open and closed state with relative ease.

 It is yet another object according to the present invention to provide a collapsible display container which is stackable with like containers when assembled, and nestable with like containers when collapsed.

20 Moreover, it is an object according to the present invention to provide a collapsible display container which is cost effective to manufacture and efficient to assemble.

25 Further, it is another object according to the present invention to provide a collapsible display container which is capable of nesting with the like containers when in a collapsed position, and is also capable of stacking with like containers when in the assembled position.

RPC0469PCA

It is still another object according to the present invention to provide a container that has a bottom which is robust and has a design which is sufficiently able to support the load placed therein.

In carrying out the above objects, features and advantages according to the present invention, provided is a collapsible display container including a base and a pair of opposed side walls each pivotably attached to the base. The side walls are orientable between an assembled position and a second position (collapsed or down position). At least one of the side walls includes a display member which is mounted to the wall. The display member is movable between an open position and a closed position. Thus, when the display member is in the open position and the at least one side wall is in the assembled position, the interior of the container is accessible through the at least one side wall.

The display member is preferably pivotably attached to the at least one side wall. The display member may also be releasably mounted to the at least one side wall. In a preferred embodiment, when the display member is in the closed position and the side wall is in the assembled position, the display member is generally co-planar with the side wall. In one embodiment, when the display member is in the closed position and the side wall is in the assembled position, one of the display member and the side wall includes a latch member and the other includes a recess for receiving the latch member. The display panel member is movable between the range of approximately 0° to 180°, and in one embodiment the open display panel member is parallel to the plane of its corresponding side wall.

The display member has a display member upper edge and the side wall has a side wall upper edge, wherein when the display member is in the closed position and the at least one side wall is in the assembled position, the display member upper edge is substantially co-linear with the side wall upper edge. Also, when the display member is in the open position and the at least one side wall is in the assembled position, the display member upper edge does not project below the plane of the base.

The collapsible container disclosed herein preferably also includes a second pair of opposed side walls each pivotably attached to the base and orientable between an assembled position and an unassembled position. Each of the second pair of opposed side walls is releasably mounted to an adjacent one of the pair of opposed side walls. One of the pair of opposed side walls and second pair of opposed side walls each includes a pair of opposed lateral flanges inwardly depending therefrom and integral therewith, each lateral flange having a latch receiver formed therein, the latch receiver including an aperture and a flexible latch hinge and having a latch release member actuable by a user. The other of the pair of opposed side walls and second pair of opposed side walls each includes a pair of opposed lateral edges, each lateral edge having a latching member attached thereto. Thus, when the container is oriented in an assembled position, each lateral flange abuts an adjacent lateral edge so that each aperture receives a corresponding latching member which is fastened into position by the latch hinge, forming a secure attachment between the first and second pairs of opposed side walls. Also, in order to return the container to a collapsed position from the assembled position, each latch release member is actuated by the user in order to release the latching member fastened therein.

The base of the container includes a first and second pair of opposed edges. The pair of opposed side walls and the second pair of opposed side walls are pivotably attached to a corresponding one of the first and second pair of opposed edges. In one embodiment, one of the first and second pairs of opposed edges are each defined by an upstanding base wall. When the pairs of side walls are oriented in the second position, they are oriented in one of an inwardly folded orientation or an outwardly folded orientation.

The container preferably has a pair of opposed display panel members attached to opposed side walls, and may also have a third or fourth display panel member on the remaining side walls.

The above objects and other objects, features, and advantages of the present invention are readily apparent from the following detailed description of the

RPC0469PCA

best mode for carrying out the invention when taken in connection with the accompanying drawings.

BRIEF DESCRIPTION OF DRAWINGS

5 FIGURE 1 of the drawings illustrates a perspective view of the collapsible container according to the present invention oriented in an assembled state;

 FIGURE 2 illustrates a side elevational view of the container of Figure 1;

10 FIGURE 3 illustrates an end elevational view of the container of Figure 1;

 FIGURE 4 illustrates a top plan view of the container of Figure 1;

 FIGURE 5 is a sectional view of the container taken along the line 5-5 of Figure 4;

15 FIGURE 6 is a sectional view of the container taken along the line 6-6 of Figure 4;

 FIGURE 7 is a bottom plan view of the container of Figure 1;

 FIGURE 8 of the drawings is a perspective view of the collapsible container of Figure 1 with the merchandising panel in a down position;

20 FIGURE 9 is a perspective view of the container of Figure 1 showing the opposed display panels of the side walls in an open position;

RPC0469PCA

FIGURE 10 illustrates two like containers according to the present invention in a stacked orientation, with the display panels of each container in an open position;

5 FIGURE 11 illustrates the container of Figure 1 with the side walls in an outwardly folded orientation;

FIGURE 12 illustrates the container of Figure 1 with the side walls in an inwardly folded orientation, wherein the opposed side walls are first folded inwardly and then the opposed end walls are folded inwardly;

10 FIGURE 13 is an enlarged perspective view of the end wall portion of Figure 12 illustrating the hinge mechanism according to the present invention for retaining the side walls and end walls to the base of the container;

15 FIGURES 14a and 14b illustrate a partial view of a second embodiment of a container according to the present invention showing the display panel between the open position (Figure 14a) and the closed position (Figure 14b), wherein in the closed position (Figure 14a) the display panel member is enclosed within the side wall, and does not extend to an outer edge of the side wall;

20 FIGURES 15a and 15b illustrate a partial view of a third embodiment of a container according to the present invention wherein the display panel member is slidably received within its corresponding side wall between a closed position (Figure 15a) and open position (Figure 15b);

FIGURE 16 is a top plan sectional view of the assembled latching system according to the present invention, and taken along line 16-16 of Figure 8, for latching together side walls and end walls, according to the present invention;

25 FIGURE 17 is a top plan sectional view of the latching system of Figure 16 in a disassembled orientation, with the side wall shown separated from the end wall;

FIGURE 18 is a bottom perspective view of the base and bottom surface according to the present invention, illustrating its design to allow for nesting of like containers when in the inwardly folded orientation, as in Figure 12;

5 FIGURE 19 is a perspective view of a plurality of containers according to the present invention which are inwardly folded as shown in Figure 12 and which are stacked together in a stacked orientation;

10 FIGURES 20a, 20b, and 20c, illustrate a plan view of two like containers according to the present invention in the inwardly folded and nested orientation as shown in Figure 19, for illustrative purposes showing the bottom surface of one container in solid lines and the end walls of the subjacent container in phantom lines, such that the bottom surface design mates with and accommodates the corresponding outer surface of the inwardly folded end walls, to provide for a stable and secure nested configuration, wherein Figures 20a-c illustrates that the bottom design may accommodate various end wall heights, including a first, 15 relatively short end wall height (Figure 20a), a second, intermediate end wall height (Figure 20b), and a third, relatively long end wall height (Figure 20c);

FIGURE 21 is a perspective view of a corner portion of container 10 according to the present invention;

20 FIGURE 22 is a sectional view taken along the line 22-22 of Figure 21;

FIGURE 23 is a sectional view similar to that shown in Figure 22, but with the end wall in an outwardly folded orientation;

FIGURE 24 is a sectional view taken along the line 24-24 of Figure 21; and

25 FIGURE 25 is a sectional view similar to that shown in Figure 24, but with the side wall in an outwardly folded orientation.

BEST MODE FOR CARRYING OUT THE INVENTION

With reference to Figure 1 of the drawings, illustrated therein is collapsible display container 10 according to the present invention. The components of container 10 are typically formed of various types of plastic or polymeric material via an injection molding or other plastic molding process suitable to this application. Container 10 may be used for the storage, transport, and display of goods, and may also be referred to as a collapsible crate. While container 10 is suitable for many uses, container 10 is particularly suitable for the storage, transport, and display of produce such as fruits and vegetables, where circulation of air and/or refrigerated gas is necessary to keep the produce fresh and consumable while it reaches the market. This circulation is fostered through the plurality of apertures 13 provided in base 12 of container 10, as shown as annular holes in Figures 1, 4, and 7, and as slots in Figures 18-21.

Container 10 includes a base member 12 having a bottom panel 14 which serves as the lower support for the container. As is best shown in the top plan view of Figure 4 and bottom plan view of Figure 7, bottom panel 14 is generally rectangular in shape and has four edges -- namely, a pair of opposed side edges 16 and 18, and a pair of opposed end edges 20 and 22. Base 12 further includes integrally molded upstanding flanges 24 and 26 (or base walls) oriented perpendicular to bottom panel 14, each defining an upper side edge 25 and 27, respectively. As is well understood in the art, the wall thickness of each of the walls and components illustrated and disclosed herein may vary depending on the intended usage and other characteristics desired from container 10.

With reference to Figure 5, illustrated herein is a sectional view of container 10 taken along the transverse centerline 5-5 of Figure 4. As shown therein, bottom panel 14 is curved between edges 16 and 18 such that it is bowed upward with a relatively slight arcuate shape, instead of having a typical flat profile. This bowed feature of bottom panel 14 serves to add stability to the container and augment the life of the container, as well as provide protection to the contents of containers stacked therebelow. Particularly, when container 10 is filled or has goods

placed therein, the weight of the goods will exert load upon bottom panel 14. Under this load, the bowed design of bottom panel 14 will tend to cause bottom 14 to flatten. This is desirable in comparison to a container having a typically flat bottom which under the same load described above, will tend to sag and bow downward, thereby, decreasing the container's strength, stability, and life, and also possibly causing damage to the contents of the container therebelow.

As shown in Figures 1-2, and 11, container 10 also includes a first pair of opposed side walls 28 and 30, which are situated opposite each other across bottom panel 14. Side walls 28 and 30 are each pivotably attached to base 12 by way of a hinging configuration or system 37 (best shown in Figure 13), located at edges (16,18) of bottom panel 15. Thus, side walls (28, 30) fold or pivot relative to base 12 at edges 16 and 18. Such hinging system 37 allows side walls 28 and 30 to be foldably positioned in three orientations: the assembled container orientation, as illustrated in Figures 1 and 8; the outwardly collapsible orientation, as illustrated in Figure 11; and the inwardly collapsible orientation, as illustrated in Figure 12. As shown in Figures 1 and 2, hinging system 37 does not extend the length of base 14 but terminates at a distance away from each upstanding flange 24 and 26, as well as a distance remote from an adjacent corresponding corner line 31.

As illustrated in Figures 1-3, and 11, container 10 further includes a second pair of opposed side walls 32 and 34. For ease of reference and discussion, second pair of opposed side walls is herein referred to as a pair of opposed end walls 32 and 34. Like side walls 28 and 30, end walls 32 and 34 are similarly pivotably attached to base 12 by way of a hinging mechanism 39 which is similar in structure to hinging mechanism 37 described above, and as shown in Figure 13. However, unlike the side walls, end walls 32, 34 are folded relative to base 12 at a distance remote from bottom panel 14. Particularly, end walls 32 and 34 are pivotably attached to upstanding flanges 24 and 26, respectively, of base 12, proximate upper edges 25, 27, respectively, at a distance remote from bottom panel 14. The height of upstanding base wall flanges 24, 26 defines the aforementioned distance from which end walls 32 and 34 are remote from bottom panel 14. As with the other walls discussed herein, end walls 32 and 34 are orientable in three positions:

RPC0469PCA

assembled shown as in Figures 1 and 8; outwardly collapsed as in Figure 11; and inwardly collapsed as in Figure 12.

As best shown in Figures 1, 11 and 12, each end wall 32 and 34 has a U-shaped cross section formed by a main end wall portion 40, and two shorter flange portions 42 and 44 integrally attached to main end wall portion 40 and located on either side of main end wall portion 40. Flange portions 42 and 44 are each oriented perpendicular to main end wall portion 40 and, in the assembled orientation of Figure 1, are directed inward toward the other end wall (32 or 34) and side walls 28 and 30. In an assembled orientation, the outer surface of flange portions are coplanar with side walls 28,30.

In accordance with the teachings of the present invention, further included in container 10 is a locking or latching system for latching side walls (28,30) together with end walls (32,34) to achieve the desired stability when container 10 is oriented in the assembled orientation, as in Figure 1. With reference to Figure 11, provided on each lateral edge (48, 50) and (52, 54) of side walls 28 and 30, respectively, is a latch member 56 extending outwardly therefrom.

By way of example with respect to Figures 5, 9, and 11, for latching purposes, shorter flanges 42, 44 of end walls 32, 34 have a latch receiving system 58 provided for receiving latch member 56 therein. Latch receiving system 58 includes a receiver member 59, latch receiving aperture 60 and a living hinge 62. Aperture 60 is appropriately sized and shaped to firmly receive latch member 56. A receiver member 59 is disposed adjacent aperture 60. Receiver member 59 is attached to end wall 32, 34 by living hinge 62, thus allowing it to be flexible over its length, and particularly actuatable in the side to side direction. Thus, as a side wall (28 or 30) is raised upwardly and an adjacent end wall (32 or 34) is raised upwardly to receive latch member 56 into the assembled orientation, aperture 60 slidably receives latch member 56, flexing living hinge 62 laterally causing receiver member 59 to move from its rest position (see Figure 17) from the rest position.

RPC0469PCA

As illustrated in the top plan sectional views of Figures 16-17, and particularly in the final assembled position of Figure 16, a projection member 61 is disposed on receiver member 59 for being received by a corresponding aperture 57 formed in latch member 56. During the assembled state, projection 61 retains latching member 56 in a secure manner and provides the stability desired for maintaining container 10 in the assembled position. The depth of flanges 42,44 allows for receiving therein a longer latch member 56 than would otherwise be possible.

As illustrated in the top plan sectional views of Figures 16 and 17, in order to collapse container 10 from the assembled orientation into the folded orientations of Figures 11 and 12, outer release member 55 (accessible from the outside of container 10) of receiver member 59 is actuated and moved laterally by the user, and projection 61 is accordingly raised from the aperture 57 in latch member 56, allowing latch member 56 (shown in phantom in Figure 16) to be released from latch receiver 58. Release member 55 is best illustrated in Figures 1, 3, and 12.

The reduced stress concentration of the latch mechanism as provided according to the present invention is further illustrated in Figures 2, 6 and 10. By example, refer to line 81 which is formed by the mating lateral edges of side wall 28 and end wall 32 (for example, the line 81 defined by lateral edge 48 of side wall 28 and flange 42 of end wall 32). The latching that takes place is spaced apart from corner line 31 which otherwise is subjected typically to relatively higher stress concentration forces.

In addition to latch member 56, each lateral edge (48,50) and (52,54) of side walls 28 and 30, respectively, may also include a first tab member 45, shown as relatively large and elongated, which projects from a lower portion of its respective edge of side walls 28 and 30 for alignment purposes. In an assembled container 10, tab member 45 is received by a corresponding opening 47 which resembles a narrow slot on shorter flanges 42, 44. The opening receives first tab member 45 in a secure fit for providing a manner by which to align and orient the

adjoining walls, as well as secondarily assisting in securely holding side walls (28 and 30) and end walls (32 and 34) upright together during the assembled orientation. Moreover, upper portion of lateral edges (48, 50) and (52, 54) of side walls 28 and 30, respectively, may also include a second tab member 49 which is relatively
5 smaller than first tab member 47. Like first tab member 47, in the assembled orientation second tab member 49 is received by a corresponding tab opening 51 formed in flanges 42 and 44 of end wall 32,34. Tab member 49 is provided generally for alignment purposes as well as to provide an additional point of engagement between the adjoining walls.

10 In keeping with the present invention, container 10 also includes at least one display panel member 70 (or merchandising panel member) to provide visibility and access to the contents of container 10 under circumstances when access to the container may not be otherwise available. Such circumstances may include a container which has like containers stacked thereon, or has other objects placed
15 thereon, such that conventional access through the upper opening of the container is difficult or inconvenient. In a preferred embodiment illustrated in Figures 1-12 herein, container 10 includes a plurality of display panel members, one embodiment of which being the pair of opposed panels members 70 and 72 illustrated in Figures 1 and 9-10, wherein container 10 is shown symmetrical about its centerlines.

20 Figure 1 illustrates panel member 70 in a closed orientation and Figure 8 illustrates display member 70 in an open orientation which allows visibility and access to the contents of container 10. Figures 9-10 illustrate both display panels 70 and 72 in an open position which allows access and visibility to container 10 from both sides. In particular, side walls 28 and 30 each include a corresponding
25 display panel 70, 72 which is generally rectangular and foldably pivots about its respective side wall between the closed position and the open position.

For purposes of an example, the following discussion refers to display panel 70, but the discussion is equally applicable to panel 72. As best shown in the first embodiment of container 10 and with reference to Figures 1 and 8, display
30 panel 70 is disposed within side wall 28 and includes an upper edge 74 which serves

RPC0469PCA

as the upper edge of side wall 28 and is generally flush and co-planar with the upper edge of the other portions of container 10, such as upper edge 73 of end walls 32, 34 and upper edge 29 of the remainder of side walls 28, 30. Note that upper edge 74 of display panel 70 is generally co-linear with upper edge 29 of side panel 28.

5 As further illustrated, when panel member 70 is in its open position (see Figures 8-10), upper surface 74 of panel member 70 is designed in terms of placement and height so that it does not project below the plane defined by bottom surface 14, but instead is preferably shorter than or flush with bottom surface 14 so that panel member 70 in the open position does not interfere with the stability of
10 base 12 on a resting surface or interfere with its stackability with other containers. Panel member 70 is pivotably attached to its respective side wall by a hinge portion 75, and which is preferably an integrally molded integral living hinge but may be any other type of hinge feasible according to the design for attaching panel member 70 to its corresponding side wall 28. For example, panel member 70 may be
15 attached its corresponding side wall by way of hinge portions 37 or 39, which are used to mount walls to base 12 herein. Of course, panel member 70 may also be removably attached to its respective side wall.

Figures 8-10 illustrate panel member 70 in an open position in which it is parallel to its corresponding side wall 28 such that it folds approximately 180°
20 and lies generally in a plane parallel with its adjacent side wall 28. However, it is contemplated that panel member 70 may be foldable and orientable at any angle between 0° and 180°, as desired. Further, while panel member 70 is shown in Figures 8-10 as being folded in an outward manner, it is also contemplated that panel member 70 may cooperate with its corresponding side wall 28 such that it is capable
25 of folding inward, again, at any angle between approximately 0° and 180°. Moreover, while panel member 70 is shown pivoted relative a substantially horizontal axis, it is also contemplated that panel member 70 may also be attached to its corresponding side wall such that it pivots around and in relation to a vertical axis. With reference again to Figure 8, it is noted that panel members 70,72 each
30 includes a lower edge 76 which corresponds to and meets with intermediate edge 77 of side wall 28, 30 at the location of living hinge 75.

RPC0469PCA

When in its closed orientation, panel member 70 is securely attached (again, preferably integrally) to its corresponding side panel 28. Figures 8-10 illustrate one method of securely latching the other portions of display panel 70 to side wall 28. Particularly, panel member 70 has a pair of opposed recessed edges 78 and 80 at its outboard edges, which correspond to and mate with a pair of opposed members 82 and 84 of side wall 28, respectively. Particularly, opposed members 82, 84 are integrally formed with outboard portions 64,66 of side wall 28. Outboard portions 64, 66 are those portions of sidewall 28 which mount with end walls 32, 34 and which are releasably mounted to panel member 70. Opposed members 82, 84 project inwardly from a corresponding edge 86,88 of side wall 28. Recessed edges 78,80 of panel member 70 each include a first and second alignment member 90 and 92, respectively, and a panel latch member 94. As panel member 70 is moved between the open position of Figures 8-10 to the closed position of Figure 1, alignment members 90,92 are received within corresponding apertures 96,98, of outboard portions 64, 66, respectively, for aligning panel member 70 with its corresponding side wall.

With reference now to Figures 1 and 6, it is illustrated that panel member 70 also includes a panel latch mechanism which is preferably finger actuable for opening panel member 70. Specifically, in the embodiment illustrated, panel member 70 is opened by releasing panel latch member 94 of latch mechanism from its corresponding aperture 100 formed in side wall members 82,84. As further shown in Figure 2, for example and not limitation, latch release mechanism 102 includes a finger actuable portion 104 and a spring portion 106 which are attached to and cooperate with latch 94 such that when a user pulls portion 104 in an inward direction, it thereby compresses spring 106 and acts to release latch 94 from its secured position in aperture 100, thereby allowing panel member 70 to be opened. Of course, it is fully contemplated that various methods may be practiced according to the present invention for retaining and attaching display members 70, 72 to its respective side wall.

Accordingly, as illustrated, panel member 70 is movable and pivotable independent of its corresponding side wall 28 to which it is attached. While plurality

RPC0469PCA

of panel members 70 and 72 are illustrated as being attached to and cooperating with side walls 28 and 30, respectively, it is fully contemplated that container according to the present invention may cooperate with one or more side and end walls (28, 30, 32 and 40) such that the container may have one, two, three or four display panels, as desired and is practicable, according to the application and use.

As illustrated in Figures 1-4 and 8-11, container 10 preferably includes a plurality of recesses 17 (or notches) around its perimeter formed in upper container edges 29, 73, and 74. As illustrated in Figure 10, container 10 is in an assembled orientation and is stacked with a like container 10' subjacent thereto. Components of container 10' similar to those of the container 10 are correspondingly numbered, with the addition of a prime (') designation. Container 10 is stacked directly above container 10' such that each of its plurality of foot tabs 15 are aligned with and are received within corresponding recesses 17' of container 10'. Such alignment between foot tab 15 and recess 17' provides additional stability and alignment to container 10 when in a stacked orientation with like container 10'. Note that when panel member 70 is shown as open in a stack of containers 10, such stability and alignment between stacked containers exists on the remaining assembled walls between corresponding feet 15 and recesses 17'. Recesses 17 are shown as being disposed and located in various locations including upper surface 74 of panel members 70, 72. In the event that one or more panel members 70 are included in container 10, and it is desired that panels 70 be in their open position, recesses 17 and corresponding feet 15 may also be located towards the corners (i.e. outboard portions 64, 66 of side walls 28, 30 and end flanges 42, 44) and away from corresponding panel members 70 so that such alignment and stability may be enhanced.

Referring to Figure 11, container 10 is illustrated in an outwardly folded configuration wherein side walls 28, 30 and end walls 32, 34 are collapsed and folded in an outward orientation. This configuration provides for a low profile. With reference now directed to Figure 12, shown therein is container 10 having side walls 28, 30 and end walls 32, 34 oriented in an inwardly collapsed or folded orientation. Again the term inwardly designates a general direction of movement of

RPC0469PCA

the various walls toward base 12 and bottom panel 14. As Figure 12 indicates, the design according to the present invention allows container 10 to be compactly folded for storage and transport. In this orientation, side walls 28 and 30 are pivoted inward via hinging mechanism 37,39 and folded in a layered fashion on top of bottom panel 14. Figure 12 illustrates side wall 28 folded first and side wall 30 subsequently folded thereupon. Subsequently end walls 32 and 34 are folded inward on top of side walls 28 and 30 via latching system 39. With reference to Figure 19 and discussed herein, container 10 may be nested with a similar container when in this inwardly folded orientation.

As shown in Figures 1-3 and 11, each of side walls (28, 30) and end walls (32, 34) include a hand opening 41 and 43, respectively, ideally suited to be used as a handle in order to carry container 10. With reference to Figures 1 and 2, container 10 also includes a pair of flexible vertical tabs 93 formed integrally with side walls 28, 30 so that a label, index card or other identifier may be inserted and held therein.

With regard to hinging systems of container 10, shown in association with base 12 of Figure 13 are the hinging systems 37 (for side walls) and 39 (for end walls). Specifically, hinging systems 37 and 39 include a plurality of lower hinge members integrally formed with base 12 to mate with and attach to upper hinge members included on the respective side walls. These hinge members are spaced apart and centered along the length of the respective edge. Mating hinge portions are spaced and centered along their respective lower edges of side walls (28,30) and end walls (32,34) for mating with corresponding lower base hinge members of the base. Of course, this type of hinge is shown by way of example and not limitation, as the hinge system utilized may be any type known or contemplated which is feasible for this use.

As illustrated in the partial perspective view of Figure 21, base 12 includes at either end of upstanding flange 24,26 an upstanding corner portion 33 (or mounting post) which projects upward past upper edges 25 and 27 and is integrally formed with upstanding flanges 24 and 26. Each corner portion 33 includes two

RPC0469PCA

openings 19 and 21 formed therein. Each corner portion 33 also defines a corner line 31. Opening 19 is located relatively lower and opening 21 is located relatively higher along the height of corner portion 33. Each co-linear pair of openings 19 is provided to receive a corresponding projection 36 (shown in phantom in Figures 22 and 23) provided at each end of a corresponding side wall (28,30) for providing an additional pivoting point for each side wall with respect to base 12. Conversely, each co-linear pair of openings 21 share an axis generally adjacent upper surface (25,27) of upstanding wall 24,26. As shown in the sectional views of Figures 22 and 23, openings 21 are provided to receive a corresponding projection or other member (similar to projection 36) provided at either end of each end wall (32,34) thereby allowing each end wall to pivot with respect to base 12. Thus openings 19 and 21 provide for an additional pivot point and anchor point along the lateral sides of each wall, thus allowing for a stable hinging configuration.

As illustrated in the sectional views of Figures 24 and 25, the lower edge of each side wall may include a relatively small detent 23 (or ridge) which is received in a corresponding channel in base 12. Referring again to Figures 22 and 23, the side walls may include a projection 53 which extends along the edge of the sidewall that mates with and corresponds to corner portion 33, and is received by a mating channel 38. These projections allow for interference between the walls the corresponding base and corner portions, such that when the walls are moving between the assembled and the collapsed orientations, the walls preferably do not fall freely, but instead require assistance from the user (however minimal). Thus, during container assembly, the user does not need to support all four walls when attempting to assemble the container.

As shown in Figures 5 and 11, side walls (28, 30) have a portion 35 that extends into the corner area and projects outboard beyond edge 48, 50 and which includes the portions that pivot in relation to corner portion 33. Figure 7 is a schematic bottom plan view of container 10 which allows for nesting of similar containers 10 on top of each other when they are in the inwardly folded orientation (as in Figure 12). This design permits an inwardly collapsed container 10 to be

RPC0469PCA

stacked on top of a like folded container so that the resulting stack-up is stable (see Figure 19).

Particularly with reference to Figures 18-20, illustrated is another embodiment of a container 310 according to the present invention, and particularly such that container 310 includes a different base and wall design, but is otherwise similar to the previous embodiments. Components similar to those of the first embodiment are correspondingly numbered, with the addition of a "3" prefix. Figures 19-20 shown the nesting orientation of lower surface 363 of bottom panel 314 engaging end walls 332', 334' of a subjacent nested container 310', the end walls having a corresponding design, allowing like containers 310 and 310' to securely nest. A more detailed illustration of the bottom surface 363 of base 312 is illustrated in the perspective view of Figure 18, illustrating its design to allow for nesting of like containers when in the inwardly folded orientation, as in Figure 12.

Figure 19 is a perspective view of a plurality of containers 310 and 310' according to the present invention which are inwardly folded as shown in Figure 12 and which are in a nested orientation. Figures 20a-20c illustrates the nesting of the container embodiment of Figure 19. Specifically, Figures 20a-c illustrate a plan view of two like containers 310 and 310' in the inwardly folded and nested orientation as shown in Figure 19. For ease of reference, bottom surface 363 of container 310 is illustrated in solid lines, while the folded end walls 332', 334' of the subjacent container 310' are shown in phantom, such that the bottom surface 363 design mates with and accommodates the corresponding outer surface of inwardly folded end walls 332', 334' to provide for a stable and secure nested configuration. In keeping with the present invention, it is fully contemplated that bottom surface 363 of base 12 (best shown in Figure 18) may be designed to provide the proper rib patterns and recesses to be capable of accommodating various end walls heights, including a first, relatively short end wall height (Figure 20a), a second, intermediate end wall height (Figure 20b), and a third, relatively long end wall height (Figure 20c). In the schematic top plan view of Figure 7, bottom surface 63 includes a drag rail 68 having a plurality of openings 69 positioned and spaced

RPC0469PCA

apart therein for providing clearance for the mating end walls 32,34 when containers 10 and 10' are in a nesting orientation.

With reference to Figures 14a and 14b, disclosed therein is a second embodiment of a container 110 according to the present invention. Components similar to those of the first embodiment are correspondingly numbered, with the addition of a "1" prefix. As illustrated, container 110 includes a display panel member 172 moveable between a first closed position (Figure 14a) and a second open position (Figure 14b). In the closed position, display panel member 172 of this embodiment is disposed within its corresponding side wall 130, and is surrounded thereby. Thus, while the first embodiment of container 10 illustrates panel member 72 having an upper surface 74 flush and generally co-planar with the remaining side wall upper surfaces, in this embodiment, upper surface 174 of panel member 172 does not extend to and is not flush or co-planar with the remaining container upper surfaces. Accordingly, when container 110 is assembled in a stacked orientation with like containers, its feet 115 are nestable with each of the corresponding recesses 117 of the lower subjacent container because no recesses 117 are absent due to a folded display panel 172. This serves to enhance the stability and integrity of the stack of containers 110. Note that in the assembled orientation, upper portion 111 of sidewall 130 is independent of panel member 172 and remains in an assembled orientation when panel member is open or closed.

It is contemplated according to the teachings of the present invention that a display panel member may be attached to its corresponding side wall in various ways in order to reach the objects and goals of the present invention. For example, as illustrated in Figures 15a and 15b, a partial container view of a third embodiment of container 210 is shown having a panel member 272. Components similar to those of the first embodiment are correspondingly numbered, with the addition of a "2" prefix. Panel member 272 is a sliding panel and which is slidably received by and within its corresponding side wall 230. As illustrated, panel member 272 slidably moves between a closed position (Figure 15a) and the open position (Figure 15b) for allowing access to the container, in the direction designated by the arrow illustrated in Figure 15a. Of course, depending on the size and

RPC0469PCA

orientation of the sliding mechanism and components, panel member 272 may be co-planar or in a plane parallel to its side wall 230. As in the second embodiment shown in Figures 14a and 14b, display panel member 272 may also be disposed within its corresponding side wall 230 such that its upper surface is not co-planar with its side wall upper surface 229, but instead so that its upper surface is positioned below the side wall upper surface.

It is understood, of course, that while the forms of the invention herein shown and described include the best mode contemplated for carrying out the present invention, they are not intended to illustrate all possible forms thereof. It will also be understood that the words used are descriptive rather than limiting, and that various changes may be made without departing from the spirit or scope of the invention as claimed below.

What Is Claimed Is:

1. A collapsible container, comprising:
a base; and
a pair of opposed side walls each pivotably attached to the base and
5 orientable between an assembled position and a second position, at least one side
wall including a display member mounted thereto movable between an open position
and a closed position,
when the display member is in the open position and the at least one
side wall is in the assembled position, the interior of the container is accessible
10 through the at least one side wall.
2. The container of claim 1, wherein the display member is
pivotably attached to the at least one side wall.
3. The container of claim 2, wherein the display member is
pivotable around a horizontal axis.
- 15 4. The container of claim 1, wherein when the display panel is in
the closed position and the at least one side wall is in the assembled position, the
display member is generally co-planar with the at least one side wall.
5. The container of claim 1, wherein the display member is
releasably mounted to the at least one side wall.
- 20 6. The container of claim 1, wherein when the display member is
in the closed position and the at least one side wall is in the assembled position, one
of the display member and the at least one side wall includes a latch member and the
other of the display member and the at least one side wall includes a recess for
receiving the latch member.
- 25 7. The container of claim 1, wherein the display panel is movable
between the range of 0° to 180°.

RPC0469PCA

8. The container of claim 1, wherein the display member has a display member upper edge and the at least one side wall has a side wall upper edge, wherein when the display member is in the closed position and the at least one side wall is in the assembled position, the display member upper edge is substantially co-linear with the side wall upper edge.

9. The container of claim 8, wherein when the display member is in the open position and the at least one side wall is in the assembled position, the display member upper edge does not project below the plane of the base.

10. The container of claim 1, further comprising a second pair of opposed side walls each pivotably attached to the base and orientable between an assembled position and an unassembled position, each of the second pair of opposed side walls releasably mounted to an adjacent one of the pair of opposed side walls.

11. The container of claim 10, wherein one of the pair of opposed side walls and the second pair of opposed side walls each includes a pair of opposed lateral flanges inwardly depending therefrom and integral therewith, each lateral flange having a latch receiver formed therein, the latch receiver including an aperture and a flexible latch hinge and having a latch release member actuable by a user.

12. The container of claim 11, wherein the other of the pair of opposed side walls and second pair of opposed side walls each includes a pair of opposed lateral edges, each lateral edge having a latching member attached thereto, wherein when the container is oriented in an assembled position, each lateral flange abuts an adjacent lateral edge so that each aperture receives a corresponding latching member which is fastened into position by the latch hinge, thereby forming a secure attachment between the first and second pairs of opposed side walls, and wherein to return the container to a collapsed position from the assembled position, each latch release member is actuated by the user in order to release the latching member fastened therein.

RPC0469PCA

13. The container of claim 10, wherein the base includes a first and second pair of opposed edges, the pair of opposed side walls and the second pair of opposed side walls pivotably attached to a corresponding one of the first and second pair of opposed edges.

5 14. The container of claim 13, wherein one of the first and second pair of opposed edges are each defined by an upstanding base wall.

15 15. The container of claim 1, wherein when the pair of side walls are oriented in the second position, they are oriented in one of an inwardly folded orientation or an outwardly folded orientation.

16. The container of claim 1, wherein the display member is slidably received by its corresponding side wall.

17. The container of claim 1, wherein base has an upwardly directed curve formed therein.

15 18. A collapsible container orientable between an assembled position and a collapsed position, comprising:

a base;

20 a pair of opposed first side walls pivotably attached to the base, at least one first side wall movable between an assembled position and a collapsed position and having attached thereto a display member orientable in a closed position and an open position;

a pair of second opposed side walls pivotably attached to the base and releasably attached to the pair of opposed first side walls,

25 wherein when the display member is in the closed position and the at least one first side wall is in the assembled position, the display member is disposed within the at least one first side wall and is generally co-planar therewith, and when the display member is in the open position and the at least one first side wall is in the assembled position, the interior of the container is accessible through the at least one first side wall.

RPC0469PCA

19. The container of claim 18, wherein the pair of opposed first side walls has a first latch portion, and the pair of opposed second side walls has a second latch portion for attaching the first side walls and second side walls when in the assembled position.

5 20. The container of claim 19, wherein the pair of opposed second side walls each has a pair of flanges inwardly depending therefrom, each flange having an aperture and a user actuatable release portion, each flange mating with a corresponding first side wall having a latch member disposed thereto, the aperture sized for slidably receiving the a corresponding latch member as the container is
10 moved from the collapsed position to the assembled position, such that to release the container from the assembled position, the user actuatable release portion is actuated by a user to release the latch member therefrom.

21. The container of claim 20, wherein the base includes a plurality of corner portions oriented perpendicular to the base and integral therewith, wherein each of the first side walls and second side walls are pivotably
15 mounted to the corner portions.

22. A collapsible container, comprising:

a base having first and second pairs of opposed edges, one of the first and second pairs of opposed edges defined by an upstanding base wall, and each of
20 the first and second pairs of opposed edges including a plurality of lower hinge members;

a first pair of opposed side walls, each having a plurality of upper hinge members for pivotably mounting to a corresponding one of the plurality of lower hinge members of the first pair of opposed edges, at least one of the first pair
25 of opposed side walls including a display member mounted thereto movable between an open position and a closed position; and


a second pair of opposed side walls releasably attached to the first pair of opposed side walls, each of the second pair of opposed side walls having a plurality of upper hinge members for pivotably mounting to a corresponding one of
30 the plurality of lower hinge members of the second pair of opposed edges,



RPC0469PCA



wherein the upper hinge members and the lower hinge members are pivotably mounted for moving the first and second pairs of opposed side walls between an up position and a down position, and

5 wherein when the display member is in the open position and the at least one of the first pair of opposed side walls is in the closed position, the interior of the container is accessible through the at least one side wall.

23. The container of claim 22, wherein each of the second pair of opposed side walls has a flange member with an aperture and a latch receiver disposed therein, such that when oriented in the assembled position, the flange
10 member abuts an adjacent lateral edge of a corresponding one of the first pair of opposed side walls so that the aperture receives a corresponding latch member of the lateral edge.












FIGURE 4












FIGURE 9


FIGURE
10

















Fig. 16




Fig. 17





FIGURE
18

FIGURE 19






Fig. 20a




Fig. 20b




Fig. 20C

